

Product Code: CL025

Description: 10AX 1 Gang Intermediate Plate Switch



General Information

Dimensions	80mm (W) x 80mm (H) x 42mm (D)
Finish	Metal Clad Grey
Insert Colour	White (WH)
Materials	Front Plate & Pattress Box: Electrophoretically Coated Steel Insert & Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive Loads)
Plate Fixing Centres	60.3mm
Terminal Size	3.5mm \varnothing
Terminal Torque	0.5Nm
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²
Intermediate	Yes
Back Box Depth	40mm Supplied
Termination Type	Screw
Earth Terminal Provided	Yes
Back Box Knockouts	5 x 20mm (2 on top, 1 on bottom, 1 on each side)
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)