

**Product Code:** CMA148PL

**Description:** 4 Gang Unfurnished Dimmer Plate & Knobs (1600W Max) - 4 Apertures



### General Information

<b>Dimensions</b>	146mm (W) x 86mm (H) x 9.5mm (D)
<b>Material Composition</b>	Front Plate & Control Button: Urea
<b>Fixing Centres</b>	120.6mm
<b>Terminal Size</b>	Dependent On Modules Fitted
<b>Terminal Torque</b>	Dependent On Modules Fitted
<b>Terminal Capacity</b>	Dependent On Modules Fitted
<b>Control Type</b>	Dependant On Module(s) Installed
<b>Back Box Depth</b>	Dependent On Modules Fitted
<b>Temperature Rating</b>	-5°C to +40°C
<b>Warranty</b>	20 Years

**Standards** BS 5733: 2010 +A1: 2014

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.  
 All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.  
 Interchangeable with dimmer modules in the MiniGrid Range.  
 Suitable for dimmer modules with M10 thread, 25mm wide housing with off set spindle.

### Interchangeable Modules

MD9014: 100W Dual Mode LED Dimmer Module  
 MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module  
 MD9010: 1-10V Analogue Rotary Dimmer Module  
 MD9022: 40-250W Leading Edge Dimmer Module  
 MD9042: 60-400W Leading Edge Dimmer Module