



CMA500



CMA501



CMA504



CMA505



CMA502



CMA503



PRW208



PRW210/
PRW211



PRC009



CMA213



PRC210



PRW213



PRC216

essentials™ Decorative covers available for PRC210, see Essentials™ page m28

45A Switches - White Rockers

- CMA500 45A 1 Gang DP Switch With White Rocker
- CMA501 45A 1 Gang DP Switch With White Rocker & Neon
- CMA502 45A 2 Gang DP Switch With White Rocker
- CMA503 45A 2 Gang DP Switch With White Rocker & Neon

Cooker Control Units - White Switches

- CMA504 45A 2 Gang DP Switch With 13A DP Switched Socket & White Rockers
- CMA505 45A 2 Gang DP Switch With 13A DP Switched Socket, White Rockers & Neons

Pull Cord Switches

- PRW208 10A 3 Pole Fan Isolation Pull Cord Switch
- PRW210 45A DP Pull Cord Switch With Mechanical 'On/Off' & Neon
- PRW211 50A DP Pull Cord Switch With Mechanical 'On/Off' & Neon
- PRW213 50A DP Round Pull Cord Switch With Mechanical 'On/Off', Neon & Pattress
- CMA213 50A DP Round Pull Cord Switch With Mechanical 'On/Off', Neon & Pattress

Pull Cord Switches

- PRC009 10AX 2 Way Ceiling Pull Cord Switch
- PRC210 10AX 2 Way Pull Cord Switch
- PRC216 16A DP Pull Cord Switch With Neon

Standards: BS EN 60669, BS 4177
 Back Box Depth: 35mm Minimum Cable Size: 45A: 1 x 16mm²
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm), 2 Gang: (146mm x 86mm x 9.5mm)

Standards: BS EN 60669
 Cable Size: 009, 208, 210: 3 x 2.5mm² / 1 x 6mm² 211: 2 x 6mm² / 1 x 25mm² 213: 2 x 6mm² / 1 x 25mm² 216: 3 x 1.5mm² / 2 x 2.5mm²
 Dimensions: PRC009: 75.5mm Dia. x 43.5mm PRC210/216: 70mm Dia. x 42mm PRW208: 86mm x 86mm x 43mm
 PRW210/211: 86mm x 86mm x 43mm PRW213: 100mm Dia. x 77mm