



CMA649/ CMA650



CMA651



CMA652



CMA653



CMA049/CMA050



CMA051



CMA052



CMA053

Fused Connection Units With Optional Flex Outlet Through The Bottom

- CMA049 3A Fused Connection Unit
- CMA050 13A Fused Connection Unit
- CMA051 13A Switched Fused Connection Unit
- CMA052 13A Switched Fused Connection Unit With Neon
- CMA053 13A Fused Connection Unit With Neon

Fused Connection Units Without Flex Outlet

- CMA649 3A Fused Connection Unit
- CMA650 13A Fused Connection Unit
- CMA651 13A Switched Fused Connection Unit
- CMA652 13A Switched Fused Connection Unit With Neon
- CMA653 13A Fused Connection Unit With Neon

Standards: BS 1363 and BS 1362 (fuse)
 Back Box Depth: 25mm Minimum Cable Size: 3 x 2.5mm² or 2 x 4mm²
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm)



CMA020



CMA021



CMA024



CMA620

Fan Isolation Switch

- CMA020 10A 3 Pole Fan Isolation Switch
- CMA021 10A 3 Pole Isolation Switch

20A DP Sink/Bath Switch

- CMA024 20A DP Sink/Bath Switch With Neon
- 3 pole and 20A DP switches are non-modular

20A Keyfob Switch

- CMA620 20A Keyfob Switch
- SP940 Spare Keyfob For CMA620

Standards: BS EN 60669
 Back Box Depth: 25mm Minimum Cable Size: 20A DP: 4 x 2.5mm² 10A 3P: 1 x 2.5mm² / 2 x 1.5mm²
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm)