

Cat No.	Description	Rating	Modules	Inner Carton
Main Switch (Isolator)				
CUSW100	Double Pole	100A	2	10
CUSW1003	Triple Pole	415V/100A	3	10
CUSW1253	Triple Pole	415V/125A	3	10



CUSW100

- Positive contact status indication
- Device capable of being locked in 'ON' or 'OFF' position using a device lock

Type B	Type C	Description	Rating	Modules	Inner Carton
MCBs					
CUMB6	CUMC6	Single Pole, Breaking Capacity 6kA	6A	1	10
CUMB10	CUMC10	Single Pole, Breaking Capacity 6kA	10A	1	10
CUMB16	CUMC16	Single Pole, Breaking Capacity 6kA	16A	1	10
CUMB20	CUMC20	Single Pole, Breaking Capacity 6kA	20A	1	10
CUMB32	CUMC32	Single Pole, Breaking Capacity 6kA	32A	1	10
CUMB40	CUMC40	Single Pole, Breaking Capacity 6kA	40A	1	10
CUMB50	CUMC50	Single Pole, Breaking Capacity 6kA	50A	1	10



CUMB6

- Positive contact status indication
- Available in type B or C
- Device capable of being locked in 'ON' or 'OFF' position using a device lock

RCBOs					
CURB6	CURC6	Single Pole, Breaking Capacity 6kA	6A 30mA	1	5
CURB10	CURC10	Single Pole, Breaking Capacity 6kA	10A 30mA	1	5
CURB16	CURC16	Single Pole, Breaking Capacity 6kA	16A 30mA	1	5
CURB20	CURC20	Single Pole, Breaking Capacity 6kA	20A 30mA	1	5
CURB32	CURC32	Single Pole, Breaking Capacity 6kA	32A 30mA	1	5
CURB40	CURC40	Single Pole, Breaking Capacity 6kA	40A 30mA	1	5



CURB6

- Positive contact status indication
- Available in type B or C
- Device capable of being locked in 'ON' or 'OFF' position using a device lock
- Additional white earth lead, to provide increased protection from earth leakage.