

FL02

20W colour switchable floodlight suitable for 9m height



Product code	Finish	Type	Wattage	Colour	Beam	lm	lm/W	lx at 1m
FL02BPCS	Black	PIR sensor	20W	3000K	120°	2200	110	832
				4000K	120°	2400	120	1040
				6500K	120°	2400	120	999
FL02BXCS	Black	Standard	20W	3000K	120°	2200	110	832
				4000K	120°	2400	120	1040
				6500K	120°	2400	120	999
FL02WPCS	White RAL9016	PIR sensor	20W	3000K	120°	2200	110	832
				4000K	120°	2400	120	1040
				6500K	120°	2400	120	999
FL02WXCS	White RAL9016	Standard	20W	3000K	120°	2200	110	832
				4000K	120°	2400	120	1040
				6500K	120°	2400	120	999
FL02APCS	Anthracite grey RAL7016	PIR sensor	20W	3000K	120°	2200	110	832
				4000K	120°	2400	120	1040
				6500K	120°	2400	120	999
FL02AXCS	Anthracite grey RAL7016	Standard	20W	3000K	120°	2200	110	832
				4000K	120°	2400	120	1040
				6500K	120°	2400	120	999

Floodlights



High efficacy of up to 120lm/W



First fix bracket for quick & easy installation



Ideal for coastal areas

Guarantee	5 years for standard & 3 years for PIR
Wattage	20W
IP rating	IP65
IK rating	IK07
Tiltable	180°
Rotatable	360°
Dimmable	No
Input	220-240V 50/60Hz
LED lifetime	50,000h L70 25,000h L70 (with PIR)
Connector	Flying lead
Ambient temperature	-40°C to 40°C
Electric class	1

