



GABAT



- BS EN 61184

Cat. no.	Description	Qty
<b>GBAT</b>	Pre-wired batten-lampholder	10
<b>GBATC</b>	Pre-wired clear base batten-lampholder	10
<b>GABAT</b>	Pre-wired angled batten-lampholder	10
<b>GABATC</b>	Pre-wired clear base angled batten-lamp holder	10

- Clear terminals for easy visibility and installation
- Ample wiring space with four knockouts
- Large capacity earth terminal
- Pendant lamp holder has integral cord grip to prevent cable pull on terminals
- Batten lamp holders (straight and angled) are pre-wired

## Fixed terminal batten holder & ceiling rose



GEBAT



- BS EN 61184
- BS 67

Cat. no.	Description	Qty
<b>GEBAT</b>	T2 batten holder 3 terminal	10
<b>GRO</b>	Ceiling rose	10
<b>GROC</b>	Clear base ceiling rose	10

- Raised mounting feet assist mounting on uneven surfaces
- Batten holders and ceiling roses share a common base assembly. Fixing centres are 50.8 mm
- Bases also include easy joist mounting facility

## Pendants & lampholder



GPEND6



- BS EN 60598-2-1
- BS EN 61184

Cat. no.	Description	Qty
<b>GPEND6</b>	Pre-wired 6" pendant	10
<b>GPEND6C</b>	Pre-wired 6" clear base pendant	10
<b>GPEND9</b>	Pre-wired 9" pendant	10
<b>GPEND9C</b>	Pre-wired 9" clear base pendant	10
<b>GLHC</b>	Lampholder with integral cord grip	20

- High heat resistance (T2 rated) to BS EN 61184:1995. (Batten holders & lamp holders only)
- Max lamp rating 150 W
- Plunger springs are enclosed in brass sleeves
- Zinc plated steel bayonet sleeve for durability

## Ceiling pull cord

Cat. no.	Description	Qty
<b>GPULLGY</b>	Grey 1.5 m pull cord with single grey bangle	10
<b>GPULLRD</b>	Red 1.5 m pull cord with twin red bangles	10