

Technical Specification

Product Code: GCBR423

Description: 10AX 3 Gang 2 Way Toggle Plate Switch



Representative Image

General Information

Dimensions	146mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket	149mm (W) x 91mm (H) x 9mm (D)
Plate Design & Finish	Georgian Rope Edge Polished Cast Brass
Gasket Colour	Supplied With Both Black & White Gasket
Switch Finish	Polished Brass
Materials	Front Plate: Cast Brass Switch Front & Nut: Cast Zinc Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon
Maximum Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive Loads)
Plate Fixing Centres	120.6mm
Terminal Size	4.9mm x 4.1mm
Terminal Torque	1.2Nm
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²
Two Way	Yes
Ingress Protection	IP20
Back Box Depth	25mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125BR for polished brass finish.