

## **Technical Specification**



Product Code: GCBR570WH Description: 13A Ingot 2 Gang Switched Socket Outlet With Single 2.1A USB Outlet





## **General Information**

Dimensions 146mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Georgian Rope Edge Polished Cast Brass

Insert & Gasket Colour White

Materials Front Plate: Cast Brass, Insert: Urea

Housing: Nylon, Switch Cover: Stainless Steel

Terminals: Brass, Terminal Screws: Steel & Yellow Passivated

Contacts: Silver "on-lay" Copper / Brass, Internal Busbars: Formed Pressed Brass

PCB: Mixed Components, Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A
Plate Fixing Centres 120.6mm
Terminal Size 5mmø

Terminal Torque 1.2Nm

**Terminal Capacity** 4 x 2.5mm<sup>2</sup> or 2 x 4mm<sup>2</sup>

Single Pole Yes
Twin Earth Terminals Yes

**USB Charging Output Total** 5V DC, 2.1A

Number Of USB Outputs 1

**USB Type** USB Type "A"

**USB Standby Current** 2mA

Product Markings USB 5V 2.1A

Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years, 1 Year Electronics

**Standards** BS 1363-2: 2016 +A1: 2018

BS EN 62368-1: 2014, BS EN 62680-1-1: 2015

**Additional Information** 

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.