


ENCLOSED SWITCHGEAR

Polycarbonate Switch Disconnectors	Page 47
Mild Steel & Stainless Steel Rotary Isolators	Page 48
DC Switching Isolators	Page 49
Rear of Panel Isolators	Page 50
Compact Switch Disconnectors and Switchfuses	Page 51
Enclosed Switch Disconnectors	Page 52-54
Fuse Switches & Cylindrical Fuses	Page 55
Enclosed Switch Fuses	Page 56-58
HRC Fuses	Page 59-62
Changeover Switches	Page 63-65
Surge Protection	Page 66-67
Auxiliary Contacts for Switchgear	Page 68
Automatic Transfer Switches	Page 69
Busbar Chambers	Page 70
MCCB Accessories	Page 71
Enclosed MCCB& Enclosed CBR	Page 72
MCCBs	Page 73
CBR 4 Pole (MCCB+RCD)	Page 74
Feild Fit Accessories	Page 74-75
Upgrade Your Point of Sale	Page 76



ENCLOSED SWITCHGEAR

Enclosed Switch Disconnectors 4 Pole - Polycarbonate



Note 7 = Early Make Contact

Part No.	Dimensions HxWxD (mm)	AC23 (A)	Terminal Capacity (mm)	Qty
IS204	126x 101x 86	20	2.5	1
IS254	126x 101x 86	25	4.0	1
IS254P-L	176x 115x 101	25	4.0	1
IS324	126x 101x 86	32	6.0	1
IS324P-L	176x 116x 101	32	6.0	1
IS404	176x 116x 101	40	10	1
IS634	176x 116x 101	63	16	1
IS804	240x 160x 122	80	25	1
IS1004	240x 160x 122	100	35	1
IS1254P	240x 160x 122	125	50	1

- BS EN 61439-1 (enclosure)
- BS EN 60947-1&3 (switch)
- IP66
- Fully rated switched neutral
- *Material - Glass fibre reinforced polycarbonate
- For accessories see page 49
- Certification -  

The Niglon IS range is suitable for 3 pole, 3 pole & switch neutral and 4 pole switching.

Discount structure on these items differs to the standard discount used throughout this catalogue.