

## CONSUMER UNIT FUSE-LINKS

TYPE L

230/240 Consumer Unit Fuse-Links to IEC 60269-3/BS 88-3 and BS 1361

Rated Voltage 240V a.c. Breaking Capacity 16.5kA a.c. Breaking Range and Utilisation Category gG



Lawson type L Fuse-Links are for use in household consumer units or other single phase installations with fault levels up to 16.5kA.

They can be fitted into Pullcap Fuse-Holders (see page 16 of the short form catalogue) or other suitable Fuse-Holders.

Note: In addition to the current ratings specified in BS 1361, additional ratings certified to BS 88 have been included to meet other requirements.



## PRODUCT DETAILS

### CURRENT RATINGS AND PRINCIPAL DIMENSIONS

List Reference	Current Rating		BS 1361 Colour Coding	Principal Dimensions			
	(A) BS 1361	(A) BS 88		L		D	
				mm	ins	mm	ins
LA2	-	2	-	23	7/8	6.35	1/4
LA5	5	-	White				
LC2	-	2	-	26	1	10.32	13/32
LC5	-	5	-				
LC8	-	8	-				
LC10	-	10	-				
LC15	15	16	Blue	29	1 1/8	12.7	1/2
LC20	20	20	Yellow				
LD6	-	6	-				
LD10	-	10	-	35	1 3/4	16.67	1/32
LD16	-	16	-				
LD20	-	20	-				
LD25	-	25	-				
LD30/32	30	32	Red	35	1 3/4	16.67	1/32
LK35	-	35	-				
LK40	-	40	-				
LK45	-	45	Green				