

NTT02

24 Hour Compact General Purpose Timeswitch with Voltage Free Contacts

Features & Benefits

- 96 Quick-Set Segments for up to 48 ON/48 OFF Programmes Per 24 Hrs
- Red LED 'Mains ON' indicator for easy viewing
- 'Traffic Light' Slide Switch for Easy ON (green), Auto (green & red) and OFF (red) Mode Indication
- Switches ON and OFF at Preset Times
- Easy to use captive segment dial
- Permanent ON/OFF control
- Fits a standard flush or surface mount box min 32mm
- Voltage Free Contacts



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Segment
Back Box Minimum Depth (mm)	32
Program Modes	24 Hour
Voltage Free Contacts	Normally Open

Data sheet

NTT02

Time / Immersion & General Purpose Timeswitches

Mounting Hole Centres (mm)	60
Standby Consumption	<1.43W
Number of Channels	1
Switch rating	16A Resistive, 8A Inductive, 1HP Motor, 750W Halogen/Fluorescent, 100W CFL, 100W LED
Shortest Switching Time	15 Minute
Programmable Slots	48 ON 48 OFF (96 Segments)
Permanent ON Facility	Yes (Slider Switch)
Cable Capacity (mm²)	1.5 - 2.5mm ² Flexible Cable
Cable Entry(s)	Back Entry

General

Weight (g)	157
Height (mm)	92
Width (mm)	92
Depth (mm)	60
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483012307
Guarantee Period	3 Years
Trade Tariff Commodity Code	9032890090

Line Diagrams

