Knightsbridge

DATASHEET




SF8900MB

Screwless 115V/230V Dual Voltage Shaver Socket - Matt Black

www.mlaccessories.co.uk

NET WEIGHT (KG)0.4FINISHMatt BlackINSERT COLOURBlackINSERT COLOURBlackDIMENSIONS (MM)Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINAL LOAD/MAX. LOADYesLOAD/MAX. LOAD20VATERMINAL CAPACITY25year(s)WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	MLA PART CODE	SF8900MB
FINISHMatt BlackINSERT COLOURBlackDIMENSIONS (MM)Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREYesDECLARATION OF CONFORMITY (HELD ON FILE)Yes	DESCRIPTION	Screwless 115V/230V Dual Voltage Shaver Socket - Matt Black
INSERT COLOURBlackDIMENSIONS (MM)Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREYesDECLARATION OF CONFORMITY (HELD ON FILE)Yes	NET WEIGHT (KG)	0.4
DIMENSIONS (MM)Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREYesDECLARATION OF CONFORMITY (HELD ON FILE)Yes	FINISH	Matt Black
DIMENSIONS (MM)Width - 87.5 Projection - 4.3 Recessed Depth - 43.4MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY25year(s)WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREYesORIGIN OF CONFORMITY (HELD ON FILE)Yes	INSERT COLOUR	Black
CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	DIMENSIONS (MM)	Width - 87.5 Projection - 4.3
CLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	MINIMUM MOUNTING BOX DEPTH	47mm
IP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	CONSTRUCTION	Construction - Premium grade steel
INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	CLASS	1
SECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY21000000000000000000000000000000000000	IP RATING	IP41
EARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	SECONDARY VOLTAGE	115/230V
TERMINAL CAPACITY $2 \times 2.5 \text{mm}^2 \text{ or } 1 \times 4.0 \text{mm}^2$ WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	EARTH TERMINAL	Yes
WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 61558-2-5ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	LOAD/MAX. LOAD	20VA
MANUFACTURED IN ACCORDANCE WITH BS EN 61558-2-5 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	TERMINAL CAPACITY	2 x 2.5mm ² or 1 x 4.0mm ²
ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	WARRANTY	25year(s)
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	MANUFACTURED IN ACCORDANCE WITH	BS EN 61558-2-5
	ORIGIN OF MANUFACTURE	China
	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832903857	EAN	5055832903857



ACCESSORIES LTD



