

## **Technical Specification**



Product Code: VPBN051BK Description: 13A Double Pole Switched Fused Connection Unit With Optional Flex Outlet





Representative Image

## **General Information**

Plate Design & Finish

Dimensions 88mm (W) x 88mm (H) x 8mm (D)

Victorian Black Nickel

Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert, Switch, Fuse Drawer & Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V∼ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

**Terminal Capacity**  $4 \times 2.5 \text{mm}^2 \text{ or } 2 \times 4 \text{mm}^2$ 

Switched Yes
Double Pole Yes
Twin Earth Terminals Yes

Fuse Fitted 13A (BS 1362)

Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C
Warranty 10 Years

**Standards** BS 1363-4: 2016 +A1: 2018

BS 1362:1973

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.