

## **Technical Specification**



Product Code: VPBR035BK **Description:** 13A 1 Gang Double Pole Switched Socket Outlet





Representative Image

## **General Information**

**Dimensions** 88mm (W) x 88mm (H) x 8mm (D)

**Dimensions With Gasket** 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Brass

Insert & Gasket Colour Black

> Materials Front Plate: Stainless Steel

Insert, Switch & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 13A Plate Fixing Centres 60.3mm Terminal Size 5mmø **Terminal Torque** 2.5Nm

**Terminal Capacity** 4 x 2.5mm<sup>2</sup>, 2 x 4mm<sup>2</sup>

Double Pole Yes Twin Earth Terminals No **Ingress Protection** IP20

25mm Minimum Back Box Depth Operational Temperature  $-5^{\circ}C$  to  $+40^{\circ}C$ 

Warranty 10 Years

**Standards** BS 1363-2: 2016 +A1: 2018

## **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.