

Technical Specification



Product Code: VPBR523WH Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet With Neon





Representative Image

General Information

Dimensions 88mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Brass

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Housing: Urea Switch Cover: Stainless Steel Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 20A

Plate Fixing Centres 60.3mm

Terminal Size 5mmø

Terminal Torque 1.8Nm

Terminal Capacity 4 x 2.5mm²

Double Pole Yes
Twin Earth Terminals Yes
Neon Indicator Yes (Red)

Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C
Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.