


# Technical Specification

**Product Code:** VPPN011WH

**Description:** 10AX 1 Gang 2 Way Plate Switch



## General Information

|                                   |   |
|-----------------------------------|---|
| <b>Dimensions</b>                 | 88mm (W) x 88mm (H) x 8mm (D)   |
| <b>Dimensions With Gasket</b>     | 91mm (W) x 91mm (H) x 9mm (D)   |
| <b>Plate Design &amp; Finish</b>  | Victorian Pearl Nickel  |
| <b>Insert &amp; Gasket Colour</b> | White   |
| <b>Materials</b>                  | Front Plate: Stainless Steel<br>Insert & Rocker Switch: Urea<br>Rear Housing: Nylon<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass<br>Earth Strap: Mild Steel<br>Gasket: Nylon |
| <b>Maximum Voltage</b>            | 250V~ 50Hz  |
| <b>Load Rating</b>                | 10AX (Suitable for Inductive Loads)   |
| <b>Plate Fixing Centres</b>       | 60.3mm  |
| <b>Terminal Size</b>              | 3.5mm $\varnothing$   |
| <b>Terminal Torque</b>            | 0.5Nm   |
| <b>Terminal Capacity</b>          | 4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>  |
| <b>Two Way</b>                    | Yes   |
| <b>Ingress Protection</b>         | IP20  |
| <b>Back Box Depth</b>             | 16mm Minimum  |
| <b>Termination Type</b>           | Screw   |
| <b>Operational Temperature</b>    | -5°C to +40°C   |
| <b>Warranty</b>                   | 10 Years  |

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

## Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Interchangeable with modules in the MiniGrid Range.