

Technical Specification



Product Code: VPPN505WH

Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet & Neons



Representative Image

General Information	
Dimensions	146mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket	149mm (W) x 91mm (H) x 9mm (D)
Plate Design & Finish	Victorian Pearl Nickel
Insert & Gasket Colour	White
Materials	Front Plate: Stainless Steel Insert & Rear Housing: Urea Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon
Maximum Voltage	250V~ 50Hz
Load Rating	45A
Plate Fixing Centres	120.6mm
Terminal Size	6mmø
Terminal Torque	2.5Nm
Terminal Capacity	1 x 16mm ²
Double Pole	Yes
Twin Earth Terminals	Yes
Neon Indicator	Yes (Red)
Ingress Protection	IP20
Back Box Depth	35mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS 4177:1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.











SCP423CH



SCP423SS







SCP423PW

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 2 Errors & Omissio pecification is subject to change w