

## **Technical Specification**



Product Code: VPPN522BK Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet





Representative Image

## **General Information**

 Dimensions
 88mm (W) x 88mm (H) x 8mm (D)

 With Gasket
 91mm (W) x 91mm (H) x 9mm (D)

Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (I

Plate Design & Finish Victorian Pearl Nickel

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert & Housing: Urea Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

 Load Rating
 20A

 Plate Fixing Centres
 60.3mm

 Terminal Size
 5mmø

 Terminal Torque
 1.8Nm

 Terminal Capacity
 4 x 2.5mm²

 Double Pole
 Yes

Twin Earth Terminals Yes

Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection IP20

Back Box Depth 25mm Minimum

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

**Additional Information**