



## **Technical Specification**

## Product Code: VPPN653BK

Description: 13A Fused Connection Unit With Neon





**Representative Image** 

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

| General Information     |   |
|-------------------------|---|
| Dimensions              | 88mm (W) x 88mm (H) x 8mm (D)   |
| Dimensions With Gasket  | 91mm (W) x 91mm (H) x 9mm (D)   |
| Plate Design & Finish   | Victorian Pearl Nickel  |
| Insert & Gasket Colour  | Black   |
| Materials               | Front Plate: Stainless Steel<br>Insert, Fuse Drawer & Housing: Urea<br>Neon Lens: Polycarbonate<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass<br>Earth Strap: Mild Steel<br>Gasket: Nylon |
| Maximum Voltage         | 250V~ 50Hz  |
| Load Rating             | 13A   |
| Plate Fixing Centres    | 60.3mm  |
| Terminal Size           | 5mmø  |
| Terminal Torque         | 2.5Nm   |
| Terminal Capacity       | 4 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>  |
| Switched                | No  |
| Twin Earth Terminals    | Yes   |
| Neon Indicator          | Yes (Red)   |
| Fuse Fitted             | 13A (BS 1362)   |
| Ingress Protection      | IP20  |
| Back Box Depth          | 25mm Minimum  |
| Operational Temperature | -5°C to +40°C   |
| Warranty                | 10 Years  |
| Standards               | BS 1363-4: 2016 +A1: 2018<br>BS 1362:1973   |
| Additional Information  | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.   |

## Page 1 of 1 Rev.1. Errors & Omissions excluded ecification is subject to change without notice