

Technical Specification

CLICK® ScolmoreGROUP

Product Code: VPSB159WH Description: Twin Isolated Coaxial Outlet





Representative Image

General Information

 $\textbf{Dimensions} \hspace{0.5cm} 88mm \hspace{0.1cm} \textbf{(W)} \hspace{0.1cm} x \hspace{0.1cm} 88mm \hspace{0.1cm} \textbf{(H)} \hspace{0.1cm} x \hspace{0.1cm} 8mm \hspace{0.1cm} \textbf{(D)}$

Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Satin Brass

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert: Urea

Earth Plate: Mild Steel Terminals: Brass Gasket: Nylon

Plate Fixing Centres 60.3mm

Isolated Yes
Shielded No

Ingress Protection IP20

Back Box Depth 16mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years, 1 Year Electronics

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com