

Technical Specification



Product Code: VPSS553WH Description: 13A Ingot Fused Connection Unit With Neon & Optional Flex Outlet





Representative Image

General Information

Dimensions 88mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Stainless Steel

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Housing: Urea

Fuse Drawer Cover: Stainless Steel

Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

Switched No
Twin Earth Terminals Yes
Neon Indicator Yes (Red)

Fuse Fitted 13A (BS 1362)

Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection IP2

Back Box Depth 25mm Minimum

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-4: 2016 +A1: 2018

BS 1362:1973

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.