

Main switch

- 100A rated current
- 230/400 rated voltage
- 10000 cycles electrical life
- 10000 operations mechanical life
- BS EN60947-3 Compliant
- Forked and Pin busbar connections


Part code:	Description	Dimensions (WxHxDmm)
WMS2100	2 pole 100A main switch	35x82x70
WMS4100	4 pole 100A main switch	70x82x70



AC & DC Rotary isolators

IP65 AC/DC Isolators 20-63A

Part code:	Description	Dimensions (WxHxDmm)
WRI3P63	3 Pole 63A AC	52.2x85x84
WRI3P32	3 Pole 32A AC	52.2x85x84
WRS4P40	4 Pole 40A AC Weatherproof	98x145x112
WRS4P32	4 Pole 32A AC Weatherproof	98x145x112
WRS4P20	4 Pole 20A AC Weatherproof	98x145x112
WRS4P63	4 Pole 63A AC Weatherproof	98x188x110
WRS4P32DC	IP66 4 Pole 32A DC	98x189x110



Twin screw main switch

- 100A Rated
- 230V 2P/400V 4P
- Twin Screw Terminal for secure connection
- Colour coded Handle

Part code:	Description	Dimensions (WxHxDmm)
WIS2100	100A 2P 2 screw terminal m/s	35x103x65
WIS4100	100A 4P 2 screw terminal m/s	70x103x65
WME2100	2 pole 100A main switch Dual top terminal screws	35x92x65

